

PRO FINE PATCH

1. Identification

Product identifier: PRO FINE PATCH
Other means of identification: ----
Recommended use: Cement-based patching compound
Restriction on use: For indoor applications only
Supplier Name: ADHESIFS PROMA INC.
9801 boul. Parkway
Anjou, Québec
Canada, H1J 1P3
Telephone: 514 852-8585
Emergency tel. number: 1 866 517-7662
Available hours: 7h30 - 16h00 Monday to Friday

2. Hazard identification

Signal word: DANGER

Product classification:



Skin corrosion - Category 1. Serious eye damage - Category 1.

Carcinogenicity - Category 1A. Reproductive toxicity - Category 1A.

Serious eye irritation - Category 2A. Skin sensitization - Category 1B.

Hazard statement(s):
H314 - Causes severe skin burns and eye damage.
H350 - May cause cancer.
H360 - May damage fertility or the unborn child.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.

Precautionary statement(s)

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust and aerosol. Wash hands thoroughly after handling and any other part of the body that may have been exposed to the product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, protective clothing, eye and face protection.

Response: IF exposed or concerned: Get medical advice. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Immediately call a doctor. Wash contaminated clothing before reuse. If eye irritation persists: Get medical advice. IF ON SKIN: Wash with plenty of water. If skin irritation or a rash occurs: Get medical advice. Take off contaminated clothing and wash it before reuse.

Storage: Store locked up.

PRO FINE PATCH

Disposal: Dispose of contents/container in accordance with local, regional, national and/or international regulations in force.

Other hazards: No other effects shown.

See toxicological information, section 11

3. Composition/ Information on ingredients

No	CAS No :	Common name and synonyms	Concentration % (w/w)
1	65997-16-2	Calcium aluminates, cement	30.00 - 60.00 *
2	65997-15-1	Portland cement	5.00 - 10.00 *
3	16828-12-9	Dialuminum trisulfate tetradecahydrate	1.00 - 5.00 *
4	14808-60-7	Silica crystalline. Silicon dioxide crystalline. Quartz	0.86
5	77-92-9	Citric acid. 2-hydroxypropane-1,2,3-tricarboxylic acid	0.10 - 1.00 *
6	10102-25-7	Dilithium sulfate hydrate	0.10 - 1.00 *

* The actual concentration range is withheld as a trade secret.

4. First-aid measures

If swallowed, irritation, any type of overexposure or symptoms of overexposure occur during use of the product or persists after use, immediately contact a POISON CENTER, an EMERGENCY ROOM or a PHYSICIAN; ensure that the product safety data sheet is available.

Eye contact: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention as soon as possible.

Skin contact: Remove contaminated clothing immediately. Wash the skin with soap and water. Thoroughly wet contaminated clothing. If irritation persists, consult a doctor.

Inhalation: Move exposed person to fresh air. Keep this person warm and lying down. Loosen tight clothing such as a collar, tie, belt or waistband. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention immediately.

Ingestion: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting unless instructed by medical personnel.

Symptoms: Red eyes, itching, blurred vision and tearing. The worker may develop cutaneous hypersensitivity. Recurrent bronchitis and permanent respiratory embarrassment. This product is irritating and corrosive to skin, eyes, respiratory and digestive tracts. The severity of symptoms can vary depending on the exposure conditions (contact time, product concentration, etc.). The main symptoms of intoxication include headache, nausea, vomiting, weakness, loss of appetite, fatigue, sweating, fever, tachycardia and dyspnea. In the most severe cases, convulsions, hyperthermic coma, liver damage are reported and sometimes death.

Effects (acute or delayed): This product is a serious irritant that may cause reversible damages to the cornea. May cause kidney damage. May cause skin sensitization. May cause lung inflammation. If on skin, this product causes severe burns. Contact with eyes may cause redness, tearing, edema, pain, corneal opacity and even blindness. Studies suggest the possibility of an increase in congenital malformations. Contains crystalline silica. Prolonged exposure to respirable crystalline silica can aggravate diseases of the respiratory system and lungs and cause silicosis. The effects of silicosis can continue to develop even after the exposure ceases and they are irreversible. In addition, the progression of lung fibrosis can also lead to the development of lung cancer.

PRO FINE PATCH

Immediate medical attention and special treatment: No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

Suitable extinguishing media: Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media: Jets of water can facilitate the spread of fire.

Specific hazards arising from the hazardous product: No specific hazard.

Hazardous combustion products: None known.

Special protective equipment and precautions for fire-fighters: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions: No action shall be taken involving any personal risk or if you do not have suitable training or protection. Evacuate surrounding areas. Do not touch or walk through spilled material. Shut off all heating and ignition sources. Avoid breathing mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Protective equipment and emergency procedures: Avoid dispersal of spilled material, runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution. Use inert absorbent or retention tubes in the event of a large spill.

Methods and materials for containment and cleaning up: Stop leak if without risk. Move containers from spill area. Contain leaks and pick up with non-combustible absorbent materials such as sand, earth or vermiculite. Then, place in an appropriate waste disposal container according to local regulations. Dispose of via a licensed waste disposal contractor.

7. Handling and storage

Precautions for safe handling: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure - obtain special instructions before use. Avoid contact with eyes, skin and clothing. Do not ingest. Avoid breathing dust. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Incompatibility: Strong oxidizing agents.

8. Exposure Controls/ Personal protection

Control parameters:

Occupational exposure limit values:

Alberta

No	CAS No :	Common name and synonyms	8-hour occupational exposure limit (TWA)		15-minute occupational exposure limit (STEL)		Ceiling occupational exposure limit	
			ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
1	65997-16-2	Calcium aluminates, cement	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
2	65997-15-1	Portland cement	Not listed	10	Not listed	Not listed	Not listed	Not listed
3	16828-12-9	Dialuminum trisulfate tetradecahydrate	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
4	14808-60-7	Silica crystalline. Silicon dioxide crystalline. Quartz	Not listed	0.025	Not listed	Not listed	Not listed	Not listed
5	10102-25-7	Dilithium sulfate hydrate	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
6	77-92-9	Citric acid. 2-hydroxypropane-1,2,3-tricarboxylic acid	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed

British-Columbia

No	CAS No :	Common name and synonyms	8-hour occupational exposure limit (TWA)		15-minute occupational exposure limit (STEL)		Ceiling occupational exposure limit	
			ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
1	65997-16-2	Calcium aluminates, cement	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
2	65997-15-1	Portland cement	Not listed	1	Not listed	Not listed	Not listed	Not listed
3	16828-12-9	Dialuminum trisulfate tetradecahydrate	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
4	14808-60-7	Silica crystalline. Silicon dioxide crystalline. Quartz	Not listed	0.025	Not listed	Not listed	Not listed	Not listed
5	10102-25-7	Dilithium sulfate hydrate	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
6	77-92-9	Citric acid. 2-hydroxypropane-1,2,3-tricarboxylic acid	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed

PRO FINE PATCH

Ontario

No	CAS No :	Common name and synonyms	8-hour occupational exposure limit (TWA)		15-minute occupational exposure limit (STEL)		Ceiling occupational exposure limit	
			ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
1	65997-16-2	Calcium aluminates, cement	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
2	65997-15-1	Portland cement	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
3	16828-12-9	Dialuminum trisulfate tetradecahydrate	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
4	14808-60-7	Silica crystalline. Silicon dioxide crystalline. Quartz	Not listed	0.10 mg/m ³ Respirable fraction	Not listed	Not listed	Not listed	Not listed
5	10102-25-7	Dilithium sulfate hydrate	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
6	77-92-9	Citric acid. 2-hydroxypropane-1,2,3-tricarboxylic acid	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed

Quebec

No	CAS No :	Common name and synonyms	8-hour occupational exposure limit (TWA)		15-minute occupational exposure limit (STEL)		Ceiling occupational exposure limit	
			ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
1	65997-16-2	Calcium aluminates, cement	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
2	65997-15-1	Portland cement	Not listed	5	Not listed	Not listed	Not listed	Not listed
3	16828-12-9	Dialuminum trisulfate tetradecahydrate	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
4	14808-60-7	Silica crystalline. Silicon dioxide crystalline. Quartz	Not listed	0.1	Not listed	Not listed	Not listed	Not listed
5	10102-25-7	Dilithium sulfate hydrate	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
6	77-92-9	Citric acid. 2-hydroxypropane-1,2,3-tricarboxylic acid	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed

Saskatchewan

No	CAS No :	Common name and synonyms	8-hour occupational exposure limit (TWA)		15-minute occupational exposure limit (STEL)		Ceiling occupational exposure limit	
			ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
1	65997-16-2	Calcium aluminates, cement	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
2	65997-15-1	Portland cement	Not listed	10	Not listed	20	Not listed	Not listed
3	16828-12-9	Dialuminum trisulfate tetradecahydrate	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
4	14808-60-7	Silica crystalline. Silicon dioxide crystalline. Quartz	Not listed	0.05 as respirable fraction	Not listed	Not listed	Not listed	Not listed
5	10102-25-7	Dilithium sulfate hydrate	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
6	77-92-9	Citric acid. 2-hydroxypropane-1,2,3-tricarboxylic acid	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed

PRO FINE PATCH

United States

No	CAS No :	Common name and synonyms	IDLH NIOSH	Regulatory Limits			Recommended Limits	
				OSHA PEL		California / OSHA PEL	NIOSH REL	ACGIH ® 2019 TLV ®
				ppm	mg/m ³	8-hour TWA (ST) STEL (C) Ceiling	Up to 10-hour TWA (ST) STEL (C) Ceiling	8-hour TWA (ST) STEL (C) Ceiling
1	65997-16-2	Calcium aluminates, cement	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
2	65997-15-1	Portland cement	5000	Not listed	15 5	10 mg/m ³ 5 mg/m ³	10 mg/m ³ 5 mg/m ³	1 mg/m ³ (no asbestos and < 1% crystalline silica)
3	16828-12-9	Dialuminum trisulfate tetradecahydrate	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
4	14808-60-7	Silica crystalline. Silicon dioxide crystalline. Quartz	50	Not listed	Not listed	0.05 mg/m ³	Ca 0.05 mg/m ³	0.025 mg/m ³ (resp.) for alpha-quartz and cristobalite
5	10102-25-7	Dilithium sulfate hydrate	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
6	77-92-9	Citric acid. 2-hydroxypropane-1,2,3-tricarboxylic acid	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed

IDLH: Immediately Dangerous to Life or Health Concentrations

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety and Health Administration

PEL: Permissible Exposure Limits

California / OSHA: California Division of Occupational Safety and Health

REL: Recommended Exposure Limits

ACGIH ®: American Conference of Governmental Industrial Hygienists

TLV ®: Threshold Limit Values

Appropriate engineering controls: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep dust concentrations below any lower explosive limits.

Individual protection measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eyes: DO NOT WEAR CONTACT LENSES. Wear anti-splash safety goggles.

Hands: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties.

Respiratory: If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Others: Wear protective clothing with long sleeves and appropriate safety shoes at all times.

9. Physical and chemical properties

Physical state: Solid

Colour: Grey

Odour: Odorless

Melting/Freezing point: Not available

Initial boiling point/boiling range: Not applicable

Flammability: Not applicable

Lower flammable/explosive limit: Not applicable

Upper flammable/explosive limit: Not applicable

Flash point: Not applicable

Auto-ignition temperature: Not applicable

Decomposition temperature: Not applicable

pH: Not applicable

Kinematic viscosity: Not applicable

Solubility (in water): Insoluble

Partition coefficient – n-octanol/water (Log Kow): Not applicable

Vapour pressure: Not applicable

Density and relative density: Not available

Relative vapour density: Not applicable

Particle characteristics: Not available

10. Stability and reactivity

Reactivity: Stable under recommended conditions of storage and handling.

Chemical stability: The product is chemically stable under normal conditions of use.

Possibility of hazardous reactions: No dangerous or polymerization reactions will not occur under normal conditions of use.

Conditions to avoid: Keep away from incompatible products (see section 7). Avoid operations producing a cloud of inorganic powders or dusts. In a room where the formation of powders or dust cannot be avoided, its accumulation must be prevented, all equipment must be earthed and non-sparking tools must be used.

Incompatible materials: None known at room temperature.

Hazardous decomposition products: None known.

PRO FINE PATCH

11. Toxicological information

	Oral	Dermal	Inhalation gases	Inhalation vapours	Inhalation dusts/mists
ATE_{product}	> 5 000 mg/kg	> 5 000 mg/kg	N/A	N/A	> 5 mg/l

No	CAS No :	Common name and synonyms	LD ₅₀ oral mg/kg	LD ₅₀ skin mg/kg	LC ₅₀ inhalation ppmV 4h - gases	LC ₅₀ inhalation mg/l 4h - vapours	LC ₅₀ inhalation mg/l 4h - dusts-mist
1	65997-16-2	Calcium aluminates, cement	> 5000	> 5000	N/A	N/A	7.6
2	65997-15-1	Portland cement	> 5000	> 5000	N/A	N/A	> 5.00
3	16828-12-9	Dialuminum trisulfate tetradecahydrate	> 5000	> 5000	N/A	N/A	> 5.00
4	14808-60-7	Silica crystalline. Silicon dioxide crystalline. Quartz	> 5000	> 5000	N/A	N/A	> 5.00
5	10102-25-7	Dilithium sulfate hydrate	500	> 5000	N/A	N/A	> 5.00
6	77-92-9	Citric acid. 2-hydroxypropane-1,2,3-tricarboxylic acid	11700	> 5000	N/A	N/A	> 5.00

Routes of exposure: This product is absorbed through the respiratory tract and by the digestive tract.

Symptoms: Red eyes, itching, blurred vision and tearing. The worker may develop cutaneous hypersensitivity. Recurrent bronchitis and permanent respiratory embarrassment. This product is irritating and corrosive to skin, eyes, respiratory and digestive tracts. The severity of symptoms can vary depending on the exposure conditions (contact time, product concentration, etc.). The main symptoms of intoxication include headache, nausea, vomiting, weakness, loss of appetite, fatigue, sweating, fever, tachycardia and dyspnea. In the most severe cases, convulsions, hyperthermic coma, liver damage are reported and sometimes death.

Delayed and immediate effects: This product is a serious irritant that may cause reversible damages to the cornea. May cause kidney damage. May cause skin sensitization. May cause lung inflammation. If on skin, this product causes severe burns. Contact with eyes may cause redness, tearing, edema, pain, corneal opacity and even blindness. Studies suggest the possibility of an increase in congenital malformations. Contains crystalline silica. Prolonged exposure to respirable crystalline silica can aggravate diseases of the respiratory system and lungs and cause silicosis. The effects of silicosis can continue to develop even after the exposure ceases and they are irreversible. In addition, the progression of lung fibrosis can also lead to the development of lung cancer.

Aspiration hazard	N/A
Skin corrosion - Skin irritation	Yes
Serious eye damage - Serious eye irritation - Eye irritation	Yes
Skin sensitization	Yes
Respiratory sensitization	N/A
Specific target organ toxicity – single exposure	N/A
Specific target organ toxicity – single exposure Category 3 Narcotic effects	N/A
Specific target organ toxicity – single exposure Category 3 Respiratory tract irritation	N/A
Specific target organ toxicity – repeated exposure	N/A

PRO FINE PATCH

No	CAS No :	Common name and synonyms	IARC	ACGIH	Mutagenicity	Effect on reproduction
1	65997-16-2	Calcium aluminates, cement	Not listed	Not listed	No effects shown.	The data do not allow for an adequate evaluation of the effects on reproduction.
2	65997-15-1	Portland cement	Not listed	A4	No effects shown.	No effects shown.
3	16828-12-9	Dialuminum trisulfate tetradecahydrate	Not listed	Not listed	No effects shown.	No effects shown.
4	14808-60-7	Silica crystalline. Silicon dioxide crystalline. Quartz	1	A1	No effects shown.	No effects shown.
5	10102-25-7	Dilithium sulfate hydrate	Not listed	Not listed	No effects shown.	May have harmful effects for the child during pregnancy.
6	77-92-9	Citric acid. 2-hydroxypropane-1,2,3-tricarboxylic acid	Not listed	Not listed	No effects shown.	No effects shown.

Cancer classification under IARC (International Agency for Research on Cancer)

- Group 1: carcinogenic to humans.
- Group 2A: probably carcinogenic to humans.
- Group 2B: possibly carcinogenic to humans.
- Group 3: not classifiable as to its carcinogenicity to humans.
- Group 4: probably not carcinogenic to humans.

Cancer classification under ACGIH (American Conference of Governmental Industrial Hygienists)

- Group A1: confirmed human carcinogen.
- Group A2: suspected human carcinogen.
- Group A3: confirmed animal carcinogen with unknown relevance to humans.
- Group A4: not classifiable as a human carcinogen.
- Group A5: not suspected as a human carcinogen.

12. Ecological information

Ecotoxicity

No	CAS No :	Common name and synonyms	%	Aquatic Ecotoxicity short term	Aquatic Ecotoxicity long term	Terrestrial Ecotoxicity
1	65997-16-2	Calcium aluminates, cement	30.00 - 60.00	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.
2	65997-15-1	Portland cement	5.00 - 10.00	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.
3	16828-12-9	Dialuminum trisulfate tetradecahydrate	1.00 - 5.00	Very toxic to aquatic life.	Very toxic to aquatic life with long lasting effects.	Harmful to the environment.
4	14808-60-7	Silica crystalline. Silicon dioxide crystalline. Quartz	0.86	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.
5	10102-25-7	Dilithium sulfate hydrate	0.10 - 1.00	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.
6	77-92-9	Citric acid. 2-hydroxypropane-1,2,3-tricarboxylic acid	0.10 - 1.00	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.

Persistence and degradability. Bioaccumulative potential. Other adverse effects

No	CAS No :	Common name and synonyms	%	Persistent	Bio-accumulation	Aquatic ecotoxicity
1	65997-16-2	Calcium aluminates, cement	30.00 - 60.00	Yes	No	Yes
2	65997-15-1	Portland cement	5.00 - 10.00	Yes	No	Yes
3	16828-12-9	Dialuminum trisulfate tetradecahydrate	1.00 - 5.00	N/A	N/A	N/A
4	14808-60-7	Silica crystalline. Silicon dioxide crystalline. Quartz	0.86	Yes	No	No
5	10102-25-7	Dilithium sulfate hydrate	0.10 - 1.00	N/A	N/A	N/A
6	77-92-9	Citric acid. 2-hydroxypropane-1,2,3-tricarboxylic acid	0.10 - 1.00	No	No	No

Degradability: N/A

Mobility in soil: N/A

13. Disposal considerations

Methods of disposal: The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

14. Transport information

	TDG	DOT	IMDG	IATA
UN Number				
Proper shipping name				
Transport hazard class(es)				
Packing group				

Canada - ERAP

Not applicable

United States - Reportable Quantities (RQ)

Not applicable

Transport in bulk (according to Annex II of the International Convention for the Prevention of Pollution From Ships, 1973, as modified by the Protocol of 1978 (MARPOL 73/78), and the International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk (IBC Code)):

N/A

Marine pollutant: No

Exemption for limited quantity: Not applicable

Other exemptions: Not applicable

Special precautions: Not applicable

15. Regulatory information

Canada

No	CAS No :	Common name and synonyms	%	DSL	NDSL	NPRI
1	65997-16-2	Calcium aluminates, cement	30.00 - 60.00	X		
2	65997-15-1	Portland cement	5.00 - 10.00	X		
3	16828-12-9	Dialuminum trisulfate tetradecahydrate	1.00 - 5.00			
4	14808-60-7	Silica crystalline. Silicon dioxide crystalline. Quartz	0.86	X		
5	10102-25-7	Dilithium sulfate hydrate	0.10 - 1.00	X		

PRO FINE PATCH

6	77-92-9	Citric acid. 2-hydroxypropane-1,2,3-tricarboxylic acid	0.10 - 1.00	X		
---	---------	--	-------------	---	--	--

United States

No	CAS No :	Common name and synonyms	%	TSCA	PROP-65	RTK
1	65997-16-2	Calcium aluminates, cement	30.00 - 60.00	X		
2	65997-15-1	Portland cement	5.00 - 10.00	X		X
3	16828-12-9	Dialuminum trisulfate tetradecahydrate	1.00 - 5.00			
4	14808-60-7	Silica crystalline. Silicon dioxide crystalline. Quartz	0.86	X	X	X
5	10102-25-7	Dilithium sulfate hydrate	0.10 - 1.00	X		
6	77-92-9	Citric acid. 2-hydroxypropane-1,2,3-tricarboxylic acid	0.10 - 1.00	X		

The classification of the product and the SDS were developed in accordance with HPR 2015 and HCS 2024.

16. Other information

Date: 2024/07/29

Version: 2

Notice to reader: The manufacturer hereby declares that the information disclosed herein have been based on governmental sites and/or raw material supplier's. The manufacturer has no control over the nature and content of such information. The manufacturer fully reproduces all the information it holds on the constituent of the product, at the time it is manufactured. The manufacturer does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. By this data sheet, the manufacturer hereby discloses all the potential dangers it has knowledge of and which might be related to the using or manipulation of the product in order to allow the proper care to be brought and use with regard to the product. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist and notification is hereby given to the user. Notice is hereby given that injury can derive therefrom if the foregoing is not respected. The manufacturer assumes no responsibility for personal and/or material damage, lost or injury of whichever nature caused or which may occur following the wrongful, inappropriate, negligent or abusive use or handling of the product or from not having read the herein contained information.