PRO COLOR SEAL™ *SANDED / UNSANDED*



2. MANUFACTURER

PROMA Adhesives Inc.
9801, Parkway, Anjou, Quebec Canada H1J 1P3
Tel.: 514.852.8585
Fax: 514.852.8225
Toll-free: 1 866.51.PROMA (77662)
Email: info@proma.ca
Web: www.proma.ca

3. PRODUCT DESCRIPTION

PRO COLOR SEAL™ is a high quality, flexible colored caulking compound for showers, sink, tub and fixture surrounds. PRO COLOR SEAL is siliconized acrylic-based that provides professional-grade performance, and is low-odor. Both sanded and unsanded caulks are available in a full color spectrum designed to match all PROMA grout colors.

Uses

- Color-matched to all PROMA grout colors
- Easy to use and apply
- Flexible and long-lasting
- Moisture, mold and mildew resistant
- Low-odor
- Nonflammable
- Stain and water resistant
- Use for floor and wall tile joint repairs and for caulking inside corners, conduits and exposed tile edges
- Use to caulk around fixtures, sinks, toilets, ceramic tile transition joints, and shower and tub surrounds
- Recommended for countertop/ backsplash transition joints
- For interior institutional, commercial and residential applications
- Meets or exceeds performance specifications of TTS-2300 and ASTM C-834
- Contributes to LEED® objectives and requirements

Packaging

310 mL (10.5 fl. oz) cartridge; sanded and unsanded

Limitations

- Do not use at temperatures below 4°C (50°F) or above 41°C (105°F).
- Do not use for EXTERIOR applications.
- Do not use for caulking joints greater than 6 mm (1/4") in width.
- Do not use for installations where constant water exposure is expected, such as swimming pools, gang showers or shower pans.

NOTICE: This product contains color pigments that may stain porous materials. Protect such materials and abutting surfaces by properly masking or shielding. Test on a separate sample or over a limited sample area first to determine the suitability of the product before using.

4. TECHNICAL DATA

Applicable Standards

For Additional Information, please refer to the most recent TCNA handbook for ceramic tile installation or the TTMAC Specification Guide 09 30 00 Tile Installation Manual, or visit our website at www.proma.ca.

WORKING PROPERTIES (@23° C [73° F] and 50% RH)	
Initial set	24 hours
Time before exposure to water	48 hours
Final set	72 hours

PHYSICAL PROPERTIES (@23° C [73° F] and 50% RH)	
VOC content	25-50 g/L
Approximate coverage per 310 mL (10.5 fl. oz)	
Thickness	**Coverage**
6 mm (1/4") bead	7.5 m (25 linear ft.)
Shelf life	
36 months at normal room temperature in its original sealed container.	

5. INSTALLATION

Surface Preparation

- Surfaces and joint spaces must be clean and free of dust, dirt, oil, paint, grease, coatings, loose particles, debris and substances that may impair adequate adhesion.
- Joint spaces must be dry and vacuum-cleaned prior to caulking.

NOTICE: Tiles and adhesives must be firmly set and thoroughly cured prior to caulking. (Typically 24 to 48 hours after installation at 23°C [73°F])

Mixing

No mixing required. PRO COLOR SEAL comes in a ready-to-use cartridge.

Application

Note: Test on a small area to determine ease of application and desired results.

1. Clean and dry area with a soft, dust-free cloth.
2. Vacuum-clean joint opening.
3. Cut the cartridge's nozzle tip to desired bead size.
4. Install the cartridge into the caulking gun.
5. Dispense sealant uniformly to completely fill joints.
6. Smooth over joint surface with wet finger if necessary.
7. Wipe away excess sealant with wet finger or clean damp cloth soon after application.

Cleaning

Clean excess caulk and spills with a soapy water solution while still fresh.

Health and Safety

Refer to the Safety Data Sheet (SDS) for complete details.

6. AVAILABILTY AND COST

PROMA products are widely available in Canada and the Northeast United States. To find a distributor of PROMA products, call **toll-free:1.866.51.PROMA.**

7. WARRANTY

PROMA warrants that this product is manufactured using quality raw materials and is of merchantable quality and suitable for the purpose for which it was intended. PROMA's liability under this warranty shall be limited to the replacement of its product proven to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising from the use of/or the inability to use this product.

8. MAINTENANCE

Product requires no special maintenance.

9. TECHNICAL SERVICE

For more detailed information on this product, please contact our technical department for proper recommendations and job field assistance. **Toll-free: 1.866.51.PROMA.**

10. FILING SYSTEM

Additional information is available upon request, or by visiting **www.proma.ca.**

PROMA Adhesives Inc.
9801, Parkway, Anjou, Quebec Canada H1J 1P3
Tel.: 514.852.8585
Fax: 514.852.8225
Toll-free: 1 866.51.PROMA (77662)
Email: info@proma.ca

© 2025 PROMA Adhesives, Inc.